



**DESCRIPTION**

PLASTIC INJECTION MOLDED ADJUSTMENT RING  
 MOLDED FROM HIGH DENSITY POLYETHYLENE AS DEFINED IN ASTM SPECIFICATION D-4976

ACTUAL RESIN PROPERTIES WILL VARY ALLOWING FOR THE UTILIZATION OF A MAXIMUM PERCENT OF RECYCLED MATERIAL

THE PERCENT OF POST CONSUMER WASTE TO INDUSTRIAL WASTE WILL VARY WITH AVAILABILITY AND PROPERTY RETENTION NEEDS

COLOR, SHADE AND UNIFORMITY WILL VARY WITH THE MIX OF THE POST CONSUMER AND INDUSTRIAL WASTE MATERIALS

DIMENSIONS SHOWN ARE NOMINAL - ACTUAL SIZE WILL VARY WITHIN ALLOWABLE TOLERANCE AND REQUIRED FIT

**DIMENSION SCHEDULE**

CONE SIZE	DIM A	DIM B	DIM C	DIM D	DIM H
24	33.50	23.75	5.00	23.25	1.25, 1.50, 2.00, 4.00
27	36.50	26.75	5.00	26.25	1.25, 1.50, 2.00, 4.00
30	39.50	29.75	5.00	29.25	1.50, 2.00, 3.25
32	41.50	31.75	5.00	31.25	2.00, 3.00
34	41.50	33.75	4.00	33.25	2.00, 3.00

APPROVAL DATE _____  BY _____	DESCRIPTION  POLYETHYLENE MANHOLE ADJUSTMENT RING FLAT DESIGN	SPECIFICATION REFERENCE	STANDARD PLATE NO.
-------------------------------------	--	-------------------------	--------------------